Transfer Solutions



JANAI<®













Transfer Solutions

Technical Specifications

 Overall Dimensions* 	2000 mm x 870 mm (L x W)
Stretcher Dimensions*	1840 mm x 660 mm (L x W)
Mattress Platform Dimensions*	1800 mm x 660 mm (L x W)
Backrest**	0° to 65°
Trendelenburg**	0° to 14°
Reverse Trendelenburg**	0° to 7°
Castor Diameter	200 mm / 125 mm
 Corner Buffer Diameter 	100 mm
Height* with 8" castor	710 mm to 910 mm (760 mm to 920 mm with polymer railing)
Height* with 5" castor	690 mm to 890 mm (735 mm to 895 mm with polymer railing)
Safe Working Load	200 Kgs
 Patient Load Bearing Capacity^ 	175 Kgs





AstirO is Engineered for Safe & Quick Intra Hospital Patient Transfer & Equipped for Emergency & Recovery Care Management

- Heavy duty non- staining, precision ball bearing swivel castors of 8" or 5" size with high-grade synthetic body for easy maneuverability
- Foot operated and centrally actuated lever at head and foot ends with multistage switching for total lock, direction lock or free mobility
- Gas spring assisted seamless adjustment of backrest, trendelenburg and reverse trendelenburg positions
- Convenient height adjustment on high quality hydraulic pump with foot operated levers on either sides of the trolley
- Two section mattress platform made of X-Ray permeable pre-laminated board, supported on strong tubular frame with removable stretcher
- Sliding multisize X-Ray cassette holder
- Individually operated SS or polymer safety side railings
- Safety corner buffers & push pull handles with rubber grippers (Available in red & blue colours)
- Provision of mounting heavy duty IV Pole at four locations
- Ample storage space







Variants

- AstirO with SS Railing
- AstirO with Polymer Railing

Standard Accessories

- SS safety head board with parking bay
- Oxygen cylinder cage
- SS heavy duty telescopic IV pole with 2 hooks
- · Safety belts (pair)

Safety Standards

Compliance for safety: International Standards

IEC 60601-2-52



Add on Accessories

- Rexine covered two section PU foam mattress, 50 mm thick
- Heavy duty IV pole (4 hooks)
- Vertical oxygen cylinder cage (epoxy coated) with SS mounting rod (for small size cylinder weighing up to 10 Kgs)

* \pm 10 mm Engineering variation. ** \pm 5° Engineering variation. ^When stretcher trolley is configured with standard accessories

 ϵ

