

Transfer Solutions



JANAK[®]
Because we care.



1710- Emergency & Recovery Trolley

Technical Specifications

	1710	1710A
Overall Approximate Dimension*	1910 mm x 755 mm, 75" x 30" (L x W)	1910 mm x 815 mm, 75" x 32" (L x W)
Stretcher Dimension*	1830 mm x 560 mm, 72" x 22" (L x W)	1845 mm x 710 mm, 73" x 28" (L x W)
Mattress Platform Dimension*	1785 mm x 560 mm, 70" x 22" (L x W)	1785 mm x 710 mm, 70" x 28" (L x W)
Backrest**	0° - 65°	0° - 65°
Trendelenburg**	0° - 18°	0° - 18°
Reverse Trendelenburg**	0° - 6°	0° - 6°
Minimum Height*	680 mm, 27"	680 mm, 27"
Maximum Height*	930 mm, 37"	930 mm, 37"
Safe Working Load	165 Kgs	165 Kgs
Patient Weight Bearing Capacity [^]	135 Kgs	135 Kgs

Add on Accessories

- Rexine covered mattress of 50 mm (2") thickness

Safety Standards

- Compliance for safety: International Standards IEC 60601-2-52

Standard Features

- Two section top with removable X-ray permeable stretcher
- Gas spring assisted trendelenburg & reverse trendelenburg positions
- Height adjustment by foot operated high quality hydraulic pump
- Raised backrest on ratchet
- 50 mm thick mattress
- Buffers at 4 corners
- High grade synthetic body castors wheels (125 mm) two with brakes & two without brakes
- Synthetic rubber covered push-pull handle
- Sliding X-ray cassette holder
- Stainless steel telescopic IV pole along with provision at 4 positions
- Pretreated and epoxy powder coated
- Swing away type stainless steel side rails
- Safety belts

* ±10 mm Engineering variation. ** ± 5° Engineering variation. ^When stretcher trolley is configured with standard accessories



Transfer Solutions



1707B- Emergency & Recovery Trolley

Technical Specifications

Overall Approximate Dimension with Moulded Handle*	1970 mm x 755 mm, 78" x 30" (L x W)
Overall Approximate Dimension*	1890 mm x 755 mm, 74" x 30" (L x W)
Stretcher Dimension*	1830 mm x 560 mm, 72" x 22" (L x W)
Mattress Platform Dimension *	1790 mm x 560 mm, 70" x 22" (L x W)
Backrest**	0° - 65°
Trendelenburg**	0° - 10°
Reverse Trendelenburg**	0° - 7°
Minimum Height*	660 mm, 26"
Maximum Height*	820 mm, 32"
Safe Working Load	165 Kgs
Patient Weight Bearing Capacity^	135 Kgs

Add on Accessories

- Rexine covered mattress of 50 mm (2") thickness
- Sliding X-ray cassette holder
- Oxygen cylinder cage

Safety Standards

- Compliance for safety: International Standards IEC 60601-2-52

Standard Features

- Two section top with removable X-ray permeable stretcher
- Trendelenburg & reverse trendelenburg positions on a smooth crank mechanism
- Height adjustment by smooth crank mechanism
- Raised backrest on ratchet
- 50 mm thick mattress
- Buffers at 4 corners
- High grade synthetic body castors wheels (125 mm) two with brakes & two without brakes
- Synthetic rubber covered push-pull handle
- Stainless steel telescopic IV pole along with provision at 4 positions
- Pretreated and epoxy powder coated
- Swing away type stainless steel side rails
- Safety belts
- Plated handle
- Supplied in semi knock down condition

* ±10 mm Engineering variation. ** ± 5° Engineering variation. ^When stretcher trolley is configured with standard accessories



Accessories and color shown in the picture may not be part of standard configuration. Technical alterations reserved in view of our continuous improvements. Midmark India Pvt. Ltd. is the licensed user of the trademark "Midmark India" and the logo. Reproduction of this catalogue in any form is liable for legal action.

Midmark (India) Private Limited

Head Office: Art Guild House, FOF, B-16, "B" Wing, 4th floor, Phoenix Market City, LBS Road, Kurla (West), Mumbai - 400 070
Toll Free: 1800 22 8020 | Tel: +91 22 4915 3000 | Fax: +91 22 4915 3100 | www.midmark.in | india@midmark.com

We are interested in growing relationships



TS-A.04.09.09.22