
Wardcare Solutions



JANAI<
Because we care.

Basic back adjustable bed with conventional head and foot boards and side railing







Basic back adjustable bed with polymer moulded head and foot boards and side railing

Basic back adjustable bed with polymer moulded head and foot boards and side railing







The BX2000 Semi Fowler Bed has the facility to raise the back section which is operated by a crank mechanism provided at the foot end of the Bed. The raising section allow the nursing staff to change positions for various activities and clinical positions with relative ease.

*The product images shown are for illustrative purpose only and not be an exact representation of the product. Accessories shown in the product image may not be part of the standard configuration.









Wardcare Solutions

Technical Specifications

Bed Frame Dimensions*	2190 mm x 920 mm, 79"x 36" (L x W)
Mattress Platform*	1880 mm x 810 mm, 74"x 32" (L x W)
Buffer to Buffer (when castors provided)*	2050 mm x 970 mm, 84"x 39" (L x W)
Buffer to Handle (L)*	2210 mm, 86"
Backrest Angle**	0°-70°
Safe Working Load	150 kgs
Patient Weight Bearing Capacity [^]	110 kgs

Standard Features

- Raised backrest
- Two section metallic perforated top
- Pre-treated and epoxy powder coated MS parts
- Provision for IV pole
- Removable handle
- Easily removable head and foot boards
- Supplied in SKD condition

Safety Standards

General Safety for Medical Beds IEC 60601-2-52

Add-On Accessories

Railings and Legs

- Collapsible type epoxy powder coated railing (pair)
- Collapsible type epoxy powder coated MS safety side railing with SS tubes (pair)
- Swing down type epoxy powder coated MS safety side railing (pair) (factory fitted)
- Collapsible type epoxy powder coated vertical safety side railing (pair)
- Collapsible type full-length type SS railing with epoxy powder coated frame (pair)
- Single set big size polymer railing (factory fitted)
- Split type polymer moulded safety side railing (pair) (factory fitted)
- H' type legs 910 mm (36") width & 600 mm (24") height with rubber shoes
- H' type legs 910 mm (36") width & 450 mm (18") height with rubber shoes
- H' type legs 910 mm (36") width & 600 mm (24") height with 125 mm high grade synthetic castors, two with brake and two without brake
- H' type legs 910 mm (36") width & 450 mm (18") height with 125 mm high grade synthetic castors, two with brake and two without brake

- Two section mattress with 4" thick PU foam of 40 density covered with PVC
- Two section mattress with 3" thick PU foam of 32 density covered with PVC
- Telescopic IV pole with 2 hooks
- · Telescopic IV pole with 4 hooks
- Orthopaedic traction pulley for trauma cases
- · Fixed polymer moulded handle
- Removable handle
- · Moulded chart holder
- · Mattress arrestor (set of 2)
- · Mosquito net poles
- 4" safety rubber buffer at four corners
- · Urine bag holder

Head and Foot Boards

- · Polymer moulded head and foot boards
- · SS laminated head and foot boards
- Conventional head and foot boards

* \pm 10 mm Engineering Variation and ** \pm 5° Engineering Variation \wedge When Bed is configured with standard accessories Note: Option of fixed polymer moulded handle available in lieu of removable handle.

 $C \in$



